

# CHORUS 836 V

## Product specification sheet

Aluminum/Magnesium inverted dome TNV tweeter.  
Extended response to 28kHz, ready for SACD.

6<sup>1</sup>/<sub>2</sub>" (165mm) Polyglass midrange.  
Highly dynamic and detailed medium.

3 x 6<sup>1</sup>/<sub>2</sub>" (165mm) Polyglass woofers.  
More power, more bass.

Front-firing ports for bass impact.

Powerflow™ multiport system.  
Powerful bass.


Down-firing port for deep bass.

Acrylic core, black mirror effect.  
Exclusive finish.

Solid MDF construction  
up to 1" (25mm) width.  
Non parallel inner wall structure.

OPC crossover.  
Perfect staging.  
New insulated Focal terminals.

Cast Aluminum base.  
Stable base.  
Adjustable spikes with key.



- ◆ High-end design, affordable luxury.
- ◆ Speakers designed and manufactured by Focal.

- ◆ A sound quality never before seen at this price level.
- ◆ Acrylic core, 2 side finishes ; Moka and Ebony.

Type	3-way bass-reflex floorstanding loudspeaker
Drivers	3x6 <sup>1</sup> / <sub>2</sub> " (165mm) Polyglass woofers 6 <sup>1</sup> / <sub>2</sub> " (165mm) Polyglass midrange 1" (25mm) TNV Al/Mg inverted dome tweeter
Frequency response (+/- 3dB)	40Hz - 28kHz
Low frequency point (- 6dB)	33Hz
Sensitivity (2.83V/1m)	92dB
Nom. impedance	8 ohms
Minimum impedance (@25°C)	3 ohms @ 110Hz
Max. power handling	250W
Power RMS	180W
Crossover frequency	250Hz / 3kHz
Dimensions (HxWxD)	45 <sup>3</sup> / <sub>16</sub> " x 11 <sup>1</sup> / <sub>8</sub> " x 14 <sup>3</sup> / <sub>4</sub> " (1148x282x375mm)
Net weight	66lbs (30kg)

Three-way, 3 woofers, 5 drivers in all... The **Chorus 836 V** has no fear of (very) large spaces. High-end in sound and shape, the power of the bass will surprise you. 836 V is nothing short of a grande dame, generous, powerful, but refined and subtle as well.



**FOCAL**  
the spirit of sound